

BESTFLEX

GRAVITY FLEXIBLE CONVEYORS



Type **BFR**
BESTFLEX
with Rollers

- Very robust Construction
- Load capacity: 220 kg/metre
- Castors Ø 127x38 mm
- Standard roller pitch 127 mm
- Available options: pitch 76 and 102 mm
- Bright zinc plated rollers Ø 35 mm
- Adjustable height: 720 to 1000 mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	4.9 m - 1.7 m
	6.1 m - 2.1 m
	7.4 m - 2.6 m
	9.8 m - 3.4 m
	Any length available
Width 750 mm	4.9 m - 1.7 m
	6.1 m - 2.1 m
	7.4 m - 2.6 m
	9.8 m - 3.4 m
	Any length available
Width 900 mm	4.9 m - 1.7 m
	6.1 m - 2.1 m
	7.4 m - 2.6 m
	9.8 m - 3.4 m
	Any length available



Type **BF/200**
BESTFLEX
with Skatewheels

- Very robust Construction
- Drive capacity: 300 kg/metre
- Castors Ø 127x38 mm
- Standard roller pitch 127 mm
- Available options: pitch 76 and 102 mm
- Zinc plated or plastic skatewheels Ø 48mm
- Adjustable height: 720 to 1000 mm

EXAMPLE	Lengths Expanded & Closed
Width 600 mm	4.9 m - 1.3 m
	6.1 m - 1.6 m
	7.4 m - 2 m
	9.8 m - 2.6 m
	Any length available
Width 750 mm	4.9 m - 1.3 m
	6.1 m - 1.6 m
	7.4 m - 2 m
	9.8 m - 2.6 m
	Any length available
Width 900 mm	4.9 m - 1.3 m
	6.1 m - 1.6 m
	7.4 m - 2 m
	9.8 m - 2.6 m
	Any length available



C O N V E Y O R S

A DURAVANT COMPANY




ProcessoSigma

Distributor
for Portugal & Poland

Processosigma, Unipessoal Lda
FMH Conveyors Portugal & Poland
Tel Portugal: +351 933 749 707
Tel Poland: +48 667 087 039
Email: info@processosigma.com
www.processosigma.pt

WE HAVE SPECIFIC SOLUTIONS FOR YOUR APPLICATION